

PERISTALTIC PUMP

MP2-R 230VAC

Data
Sheet

DESCRIZIONE

- ✓ Peristaltic pump with flow rate regulation
- ✓ PP body reinforced with 30% talc
- ✓ Polycarbonate front panel
- ✓ Standard 230 Vac power supply
- ✓ 10-100% speed regulation
- ✓ 100 % Made in Italy
- ✓ CE regulation compliant



OPTIONAL

- ✓ ON / OFF switch
- ✓ SCHUKO plug
- ✓ Level probe predisposition

DESCRIPTION		
	Standard Material	Upon Request
Versione standard		
Pump body	PP polipropilene with 30 %glass	-----
Roller	DELRIN	-----
Tube	Santoprene	Silicon
Power Supply	230 v 50 – 60 Hz	-----
Consumption	35 Watts	-----
Net Weight	0,5 kg.	-----
Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	-----
Standard Version	230 Vac	24 VCC
DETERGENCY KIT		
	DETERGENT	RINSE AID
Suction tube	PVC 4 x 6	PVC 4 x 6
Delivery tube	PVC 4 x 6	PE 4 x 6
Injection fitting	PP 90°	1/8" ACCIAIO
Foot filter	AISI Rubber Holder	AISI Rubber Holder

PERISTALTIC PUMP

MP2-R 230VAC

Data Sheet

SPECIFICHE TECNICHE											
Standard	Max lt/h	pressure		Max cc / min	Tube	Dimensio ns	Pump body	Watt	RPM	Weight	
		Bar	PSI							kg.	Lbs
VERSION 230VAC											
1,5 - 01	1,5	01	14,7	25	Santoprene	5,8 x 9,4	PP	35	10	0,5	1,2
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	40	0,5	1,2
06 - 01	06	01	14,7	100	Santoprene	5,8 x 9,4	PP	35	40	0,5	1,2
01 - 03	01	03	44,1	16,67	Silicone	5 x 10	PP	35	20	0,5	1,2
12 - 01	12	01	14,7	200	Santoprene	5,8 x 9,4	PP	35		0,5	1,2
20 - 01	20	01	14,7	334	Santoprene	5,8 x 9,4	PP	35		0,5	1,2

